



NOTES:

1. ANY 101 AND 202 DWGS WITH WIRING SUPERCEDE THIS DWG.
2. STANDARD WIRING IS 24 AWG, TEFLON SUPERFLEX.
3. FLYING LEADS ARE 12" LONG PER CUSTOMER REQUEST.

REV#	DESCRIPTION	ECR NO.	BY:	DATE:	APR'D	REV:	DESCRIPTION	ECR NO.	BY:	DATE:	APR'D
14	REDRAWN; REVISED MG21V (NS2)	3713	JH	01/20/10	DB	18	ADDED RHN-09 & RHNC-09	4236	ND	01/05/12	DB
15	ADDED BH-105	3768	KY	03/31/10	DB	19	ADDED MG9, DELETED BH01M	20.350	KY	05/30/12	DB
16	REVISED RH-01/02/03/04/05; RENAMED TO RHN/RHNC DESIGNATIONS	3904	ND	09/24/10	DB	20	DELETED 4-20mA FROM MG13A	377.170	AC	06/24/16	DB
17	TH20 WAS MG20; TH25 WAS MG25	4042	KY	04/07/11	DB						

J.R.MERRITT CONTROLS, INC.
STRATFORD, CT 06615

THIS DOCUMENT CONTAINS DATA WHICH IS CONFIDENTIAL AND PROPRIETARY TO JRM INC. NO DISCLOSURE, REPRODUCTION, OR ANY USE OF ANY PART OF THIS DOCUMENT MAY BE MADE WITHOUT THE WRITTEN PERMISSION OF JRM INC.

JRM P/N: N/A
DRAWN: JH DATE: 01/20/10
APPROVED: DB DATE: 01/20/10
PUB NO: WEB DOC

CUSTOMER: J.R. MERRITT CONTROLS, INC.
QUOTE NO: JOB NO: REF NO: SCALE: N/A
DESCRIPTION: STANDARD HANDLE WIRING SHEET: 1 OF 1
DWG NO: B25.101.5536 REV: 20 SIZE: B

5536