

NSO-0 ROTARY SWITCH

NSO-0 Rotary Master Switch features the same rugged design components and versatility as the NSO series of Joysticks.



SPECIFICATIONS

GENERAL DATA

Output Options	Contacts, Potentiometer, Encoder, 4-20mA & Transformer
Handle Action	Spring Return, Friction Brake or Maintained
Handle Travel	+/- 36 degrees each axis
Max of Steps	Up to 7-0-7 or 0-16 positions
Handle Compatibility	Teardrop, pistol grip & chrome steel ball lever
Life	10 million cycles
Materials	Aluminum body and nickel chromium yoke.
Est. Shipping Weight	4 lbs.
Est. Shipping Dimensions	10 in. x 10 in. x 10 in.

MOUNTING DATA

Mounting Style	Panel (from below)
Mounting Footprint	2.84" x 2.84" See literature for additional mounting specifications

ENVIRONMENTAL DATA

IP Rating	Up to IP66 / Nema 4x (with cast enclosure & round nameplate)
Operating Temperature	-13 to +158 degrees F [-25 to +70 degrees C]
Storage Temperature	-40 to +158 degrees F [-40 to +70 degrees C]


ELECTRICAL DATA

Contact Specifications	Switch Type: Double Pole Snap-In Contact Blocks
	Max. Number: Up to 10 contact blocks (20 circuits)
	Max. Switching Capacity: Making - 100 amps Breaking - (0.7PF) 240V 80 amps
	Rating (AC): Continuous 16 amps @ 240V Resistive 8 amps @ 240V Inductive 6 amps @ 240V
	Termination: Captive Saddle Clamp
	Max. Wire Size: 12 AWG
Additional Specifications	Reference product literature for additional specifications

Technical Drawings

Dimensional


All dimensions in inches [mm] and are subject to change.



NSO-0 overall dimensions

Mounting

All dimensions in inches [mm] and are subject to change.



Standard and NEMA 4 panel mounting details